

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN BREAKER WITH 20 1-INCH SPACES ALLOWING MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (100A) 22KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1 ENCLOSURE FOR INDOOR USE.

| General technical data | |
|------------------------------------------------------|--------------------------------------------------------|
| configuration of the busbars | ALUMINUM BUS |
| number of circuits in a trunking unit | 40 |
| phase number | 1 |
| suitability for operation | RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION |
| Electricity | |
| ampacity | 100 A |
| voltage between phase and Ground (GND) rated value | 120 V |
| voltage between phase and phase rated value | 240 V |
| Model | |
| product brand name | SIEMENS |
| product sub brand name | LOAD CENTERS |
| product type designation | PLUG-ON NEUTRAL READY STANDARD SERIES |
| special product feature | GREY TRIM |
| Mechanical Design | |
| number of modular width units for installation width | 20 |
| size of the circuit-breaker | 100A |
| General product approval | |
| certificate of suitability | UL |

last modified:

7/9/2021 

